

Catálogo de Produtos



Proportional flow control valve 2-way versionType 2FRE 6...RC

BEIJING HUADE HYDRAULIC INDUSTRIAL GROUP CO.,LTD.

up to 21 MPa

Replaces:

Features:

- Valve with a pressure compensator for the pressure compensated control of a flow

Size 6

- Actuation via a proportional solenoid
- With electrical position feedback of the control orifice
- The position transducer coil can be axially moved making the zero point adjustment of the control orifice easy, without having to touch the electronics (electrical-hydraulic)
- Flow control is possible in both directions by using a rectifier sandwich plate



up to 25 L/min

Functional, section, symbol

The type 2FRE ...proportional flow control valves have a 2-way function. They can, from a applied electrical command value, regulate flow which is pressure and temperature compensated.

They basically comprise of the housing (1), proportional solenoid with inductive position transducer (2), measuring orifice (3), pressure compensator (4) as well as the optional check valve (5).

Proportional flow control valve 2FRE 6 B:

The setting of the flow is determined (0 to 100 %) at the command value potentiometer. The applied command value adjusts, via the amplifier as well as the proportional solenoid, the measurement orifice(3). The position of the measurement orifice (3) is obtained by the inductive position transducer. Any deviations from the command value are compensated for by the feedback control.

The pressure compensator (4) holds the pressure drop at the measurement orifice (3) at a constant value. The flow is, therefore load compensated.

The small temperature drift is achieved due to the design of the measurement orifice.

At a 0 % command value the measurement orifice is closed.

In the case of a loss of power or a cable break at the position transducer the measurement orifice closes.

From a 0 % command value a jump free start is possible. Via two ramps within the electrical amplifier, it is possible to delay the opening and closing of the measurement orifice.

Via the check valve (5) a free flow is possible from B to A.



Proportional flow control valve type 2FRE 6 A:

The function of this valve is in principle the same as valve type 2FRE 6 B :

To suppress the start-up jump when the measurement orifice (3)(command value > 0 %) is open, there is provision for the pressure compensator (4) to be held closed via port P (6). The internal connection (7) between port A and the pressure compensator (4) is plugged. Via the external port P (6) the pressure in port P, before the directional valve (8) acts on the pressure compensator (4) and holds it against the spring force (9) in the closed position. If the directional valve (8) is switched over from P to B, then the pressure compensator(4) moves from the closed position into the regualting position and the start-up jump is thereby avoided.



Ordering details





Symbols: Proportional flow control valve (simplified, complete)

		A B P	A B P
Type 2FRE6BM	Type 2FRE6BR	Type 2FRE6AM	Type 2FRE6AR
A B		A R B	A B B

Rectifier sandwich plate:



Technical data (for applications outside these parameters, please consult us!)

			purun		, picase coi	isuit us.j		
Hydraulic								
Max. permissible operating pressure, port A			21 (port A)					
Flow q _v max. (L/min) -	Туре	2QE	3	Q	6Q	10Q	16Q	25Q
		2	;	3	6	10	16	25
	to 10MPa	0.015	0.015		0.025	0.05	0.07	0.1
$ Flow q_{v} flim. (L/flim) - k k k k k k k k$	to 21MPa	0.025	0.0)25	0.025	0.05	0.07	0.1
Max. leakage flow at Δ	$P (A \rightarrow B)$				•			
command value 0%(L/min)	5MPa	0.004	0.0	004	0.004	0.006	0.007	0.01
(measured at $v = 36^{-6}$	10MPa	0.005	0.0	005	0.005	0.008	0.01	0.015
\times 10m ² /s and t=50°C	21MPa	0.007	0.0	007	0.007	0.012	0.015	0.022
Minimum pressure differential (MPa)			0.6 to 1					
$\triangle p$ free return flow (B \rightarrow A)			see diagram on page 69					
Pressure flow relationship: inlet/outlet pressure			see diagram on page 69					
Flow stability			see diagram on page 69					
Hysteresis			$<\pm$ 1%Q $_{\sf max}$					
Repeatability			< 1%Q _{max}					
Degree of contamination (µ m)			\leq 20 (We recommend a filter with a minimum retention rate of 10)					
Pressure fluid			Mineral oil(for NBR seal), Phosphate ester (for FPM seal)					
Viscosity range (mm ^{2/} S)			2.8 to 380					
Pressure fluid temperature range (°C)			-20 to +70					
Installation						optional		
Electrical								
Voltage type						DC		

Voltage type		DC
Coil resistance of solenoid	(Ω)	Cold value at 20 $^\circ$ C 5.4 , Max. warm value 8.2
Coil resistance of transducer	(Ω)	at 20℃ (-56、 Ⅱ -56、 Ⅲ -112
Max. Power	(VA)	50
Inductivity	(mH)	6 to 8
Oscillator frequency	(KHz)	2.5
Surroundubgs temperature	(°C)	Max.50
Amplifier		VT-5010S30 Demand of insulation IP65

Frequency response characteristic curve

Input signals (%)	Qmin=to=Qmax Tu+Tg(ms)	Qmax=to=Qmin Tu+Tg(ms)
0-100	50	60
10-90	45	50
25-75	40	45



Relationship of the flow to the command value(Pnom =50 MPa)









Huade América

0.3

0.2 0.1

5

10

Flow in L/min

15

20

25

Unit dimensions:



HUADE AMÉRICA

CEP : 03162-020 RUA HIPÓDROMO 1445 – MOOCA, SÃO PAULO, SP, BRASIL TEL : (11) 3186-5959 huade@huade.com.br www.huade.com.br

Huade América